

**Trade name : Lithofin CEMENT-AWAY**

Revision date : 30.01.2019

Version (Revision) : 4.0.2 (4.0.1)

Print date : 11.02.2019

**SECTION 1: Identification of the substance/mixture and of the company/ undertaking****1.1 Product identifier**

Lithofin CEMENT-AWAY

**1.2 Relevant identified uses of the substance or mixture and uses advised against  
Relevant identified uses**

Mixture Washing and cleaning products, acidic

**1.3 Supplier (manufacturer/importer/only representative/downstream user/distributor)**

**Distributor :** CDK Stone NZ Ltd.  
Street : 2/40 Canaveral Drive  
Postal code/city : NZ Auckland 0632  
Telephone : +64 9 4750495  
Telefax : +64 9 4792424  
Contact : Technical Department  
E-mail: sales@cdkstone.co.nz

Emergency telephone number:  
+0800 764766  
(Only available during office hours)

**Supplier :** Lithofin AG  
Street : Heinrich-Otto-Str. 36  
Postal code/city : 73240 Wendlingen  
Telephone : +49 (0)7024 9403-0  
Telefax : +49 (0)7024 9403-40  
Contact : Technical Department  
E-mail: info@lithofin.de

Emergency telephone number:  
+49 (0)7024 9403-0  
(Only available during office hours)

**1.4 Emergency telephone number**

see section 1.3

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP]**

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

Skin Corr. 1B ; H314 - Skin corrosion/irritation : Category 1B ; Causes severe skin burns and eye damage.

Met. Corr. 1 ; H290 - Corrosive to metals : Category 1 ; May be corrosive to metals.

STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.

**Additional information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Results from in vitro test for skin corrosivity/irritancy: Skin Corr. 1B (OECD 435)

**Remark**

Full text of H- and EUH-phrases: see section 16.

**2.2 Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]****Hazard pictograms**

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin CEMENT-AWAY

**Revision date :** 30.01.2019

**Version (Revision) :** 4.0.2 (4.0.1)

**Print date :** 11.02.2019



Corrosion (GHS05) · Exclamation mark (GHS07)

## Signal word

Danger

## Hazard components for labelling

HYDROGEN CHLORIDE ; CAS No. : 7647-01-0

FORMIC ACID ; CAS No. : 64-18-6

## Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

## Precautionary statements

P102 Keep out of reach of children.

P234 Keep only in original packaging.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

## Other labelling

### 2.3 Other hazards

#### Adverse human health effects and symptoms

Due to its pH value (see section 9), irritation of the skin and eyes cannot be ruled out.

### 2.4 Additional information

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

HYDROGEN CHLORIDE ; REACH registration No. : 01-2119484862-27-xxxx ; EC No. : 231-595-7; CAS No. : 7647-01-0

Weight fraction :  $\geq 15 - < 20$  %

Classification 1272/2008 [CLP] : Met. Corr. 1 ; H290 Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 STOT SE 3 ; H335

FORMIC ACID ; REACH registration No. : 01-2119491174-37-xxxx ; EC No. : 200-579-1; CAS No. : 64-18-6

Weight fraction :  $\geq 10 - < 15$  %

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Skin Corr. 1A ; H314 Eye Dam. 1 ; H318

#### Additional information

All ingredients of this mixture are (pre)registered according to REACH regulation.

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin CEMENT-AWAY

**Revision date :** 30.01.2019

**Version (Revision) :** 4.0.2 (4.0.1)

**Print date :** 11.02.2019

respiration. In case of respiratory tract irritation, consult a physician.

### In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. Do not wash with: Cleaning agent, acidic Cleaning agent, alkaline Solvents/Thinner

### After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

### After ingestion

Call a physician immediately. Keep at rest. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting.

### Self-protection of the first aider

First aider: Pay attention to self-protection!

## 4.2 Most important symptoms and effects, both acute and delayed

No information available.

## 4.3 Indication of any immediate medical attention and special treatment needed

### Notes for the doctor

Treat symptomatically.

### Special treatment

First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water spray ABC-powder Foam

#### Unsuitable extinguishing media

Full water jet Strong water jet

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

Carbon monoxide Carbon dioxide (CO<sub>2</sub>) Hydrogen chloride (HCl)

### 5.3 Advice for firefighters

Use suitable breathing apparatus.

#### Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

### 5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases. The product itself does not burn. Coordinate fire-fighting measures to the fire surroundings.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment (refer to section 8). Provide adequate ventilation. Remove persons to safety.

### 6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

### 6.3 Methods and material for containment and cleaning up

#### For cleaning up

Suitable material for taking up: Universal binder

Clean contaminated articles and floor according to the environmental legislation. Retain contaminated washing water and dispose it. Dispose of waste according to applicable legislation.

#### Other information

**Trade name : Lithofin CEMENT-AWAY**

Revision date : 30.01.2019  
Print date : 11.02.2019

Version (Revision) : 4.0.2 (4.0.1)

Clear spills immediately.

**6.4 Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

When using do not eat, drink, smoke, sniff.

**Protective measures**

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists  
Skin contact Eye contact Wear personal protection equipment (refer to section 8). Always close containers tightly after the removal of product. Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Technical measures and the application of suitable work processes have priority over personal protection equipment.

**Measures to prevent fire**

The product is not: Flammable Usual measures for fire prevention.

**Fire class :** -

**Shake well before use** nein

**Advices on general occupational hygiene**

P362+P364 - Take off contaminated clothing and wash it before reuse.

**7.2 Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep/Store only in original container. The floor should be leak tight, jointless and not absorbent. Ensure adequate ventilation of the storage area.

**Hints on joint storage**

**Storage class (TRGS 510) :** 8B

**Protect from frost** nein

**Recommended storage temperature** 5 - 25 °C

**Further information on storage conditions**

Keep locked up and out of reach of children. Keep container tightly closed in a cool, well-ventilated place.

**7.3 Specific end use(s)**

**Recommendation**

Observe technical data sheet. Observe instructions for use.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational exposure limit values**

HYDROGEN CHLORIDE ; CAS No. : 7647-01-0

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 2 ppm / 3 mg/m<sup>3</sup>

Peak limitation : 2(I)

Remark : Y

Version : 01.03.2018

Limit value type (country of origin) : STEL ( EC )

Limit value : 10 ppm / 15 mg/m<sup>3</sup>

Version : 31.01.2018

Limit value type (country of origin) : TWA ( EC )

Limit value : 5 ppm / 8 mg/m<sup>3</sup>

Version : 31.01.2018

FORMIC ACID ; CAS No. : 64-18-6

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin CEMENT-AWAY

**Revision date :** 30.01.2019

**Version (Revision) :** 4.0.2 (4.0.1)

**Print date :** 11.02.2019

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 5 ppm / 9,5 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : Y  
Version : 17.10.2017  
Limit value type (country of origin) : TWA ( EC )  
Limit value : 5 ppm / 9 mg/m<sup>3</sup>  
Version : 07.02.2006

## 8.2 Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation of the storage area.  
Technical measures and the application of suitable work processes have priority over personal protection equipment.

### Personal protection equipment

#### Eye/face protection

##### Suitable eye protection

Eye glasses with side protection goggles

##### Required properties

DIN EN 166

#### Skin protection

##### Hand protection

**Suitable gloves type :** Gloves with long cuffs

**Suitable material :** Data apply to the main component. Butyl caoutchouc, 0,5mm, >8h; FKM (fluoro rubber), 0,7mm, >8h;

**Recommended glove articles :** Manufacturer KCL GmbH/Eichenzell-Germany; Ansell/Yarra City-Australia Or comparable articles from other companies.

**Additional hand protection measures :** Check leak tightness/impermeability prior to use.

**Remark :** Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams are not substitutes for body protection.

##### Body protection

Protective clothing.

**Suitable protective clothing :** Chemical protection clothing Chemical resistant safety shoes

**Required properties :** acid-resistant.

Protective clothing. : DIN EN ISO 20345 DIN EN 13034 DIN EN 14605

footwear : DIN EN 14404

**Remark :** Barrier creams are not substitutes for body protection.

#### Respiratory protection

Usually no personal respiratory protection necessary. Respiratory protection necessary at: insufficient ventilation aerosol or mist formation. high concentrations spray application

##### Suitable respiratory protection apparatus

Combination filtering device (EN 14387) Half-face mask (DIN EN 140) ABEK-P1

##### Remark

Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

### General health and safety measures

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink, smoke, sniff. Keep away from food, drink and animal feeding stuffs. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to re-use. Wash hands before breaks and after work. Apply skin care products after work. Do not breathe gas/fumes/vapour/spray.

## SECTION 9: Physical and chemical properties

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

## Trade name : Lithofin CEMENT-AWAY

Revision date : 30.01.2019  
Print date : 11.02.2019

Version (Revision) : 4.0.2 (4.0.1)

### 9.1 Information on basic physical and chemical properties

**Appearance :** Liquid

**Colour :** light yellow

**Odour :** stinging

#### Safety relevant basis data

|  |              |         |                |                   |   |
|--|--------------|---------|----------------|-------------------|---|
| <b>Melting point/melting range :</b>             | ( 1013 hPa ) | <       | -13            | °C                |   |
| <b>Initial boiling point and boiling range :</b> | ( 1013 hPa ) | approx. | 106            | °C                |   |
| <b>Decomposition temperature :</b>               | ( 1013 hPa ) |         | not determined |                   |   |
| <b>Flash point :</b>                             |              |         | not applicable |                   | closed cup<br>(EN ISO 3679)                 |
| <b>Ignition temperature :</b>                    |              |         | not determined |                   |   |
| <b>Sustaining combustion</b>                     |              |         | No             |                   | UN Test L2:Sustained<br>combustibility test |
| <b>Lower explosion limit :</b>                   |              |         | not determined |                   |   |
| <b>Upper explosion limit :</b>                   |              |         | not determined |                   |   |
| <b>Vapour pressure :</b>                         | ( 50 °C )    | <       | 3000           | hPa               |   |
| <b>Density :</b>                                 | ( 20 °C )    |         | 1,12           | g/cm <sup>3</sup> | Pyknometer (DIN EN<br>ISO 2811-1)           |
| <b>Solvent separation test :</b>                 | ( 20 °C )    | <       | 3              | %                 | Test L1: Solvent<br>separation test (UN)    |
| <b>Water solubility</b>                          | ( 20 °C )    |         | miscible       |                   |   |
| <b>pH :</b>                                      |              | approx. | 0              |                   | DIN 19268                                   |
| <b>log P O/W :</b>                               |              |         | not determined |                   | (Mixture)                                   |
| <b>Flow time :</b>                               | ( 23 °C )    | <       | 15             | s                 | ISO cup 4 mm<br>(DIN EN ISO 2431)           |
| <b>Odour threshold :</b>                         |              |         | not determined |                   |   |
| <b>Vapourisation rate :</b>                      |              |         | not determined |                   |   |
| <b>VOC content-EC</b>                            |              | approx. | 14,6           | Wt %              | *   |
| <b>VOC-France</b>                                |              |         | not applicable |                   | Décret no 2011-321 du<br>23 mars 2011       |

(\* VOC-EC = „Volatile organic compound (VOC)“ means any organic compound having an initial boiling point less than or equal to 250°C measured at a standard pressure of 101,3 kPa; VOC-value in g/L)

### 9.2 Other information

None

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

### 10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

### 10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

### 10.4 Conditions to avoid

Stable under recommended storage and handling conditions.

### 10.5 Incompatible materials

The product develops hydrogen in an aqueous solution in contact with metals.

### 10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

**Trade name :** Lithofin CEMENT-AWAY

**Revision date :** 30.01.2019

**Version (Revision) :** 4.0.2 (4.0.1)

**Print date :** 11.02.2019

### Acute effects

There are no data available on the preparation/mixture itself. Data apply to the main component.

#### Acute oral toxicity

Parameter : LD50 ( FORMIC ACID ; CAS No. : 64-18-6 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 1210 mg/kg

#### Acute inhalation toxicity

Parameter : LC50 ( HYDROGEN CHLORIDE ; CAS No. : 7647-01-0 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 3124 ppm

### Specific symptoms in animal studies

There are no data available on the preparation/mixture itself.

### Irritant and corrosive effects

#### Assessment/classification

Causes serious eye damage. Causes severe burns. Results from in vitro test for skin corrosivity/irritancy: Skin Corr. 1B (OECD 435)

### Sensitisation

There are no data available on the preparation/mixture itself.

### Repeated dose toxicity (subacute, subchronic, chronic)

There are no data available on the preparation/mixture itself.

### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

#### Carcinogenicity

There are no data available on the preparation/mixture itself.

#### Other information

No indication of human carcinogenicity.

#### Germ cell mutagenicity

There are no data available on the preparation/mixture itself.  
No indications of human germ cell mutagenicity exist.

#### Reproductive toxicity

There are no data available on the preparation/mixture itself.

#### Other information

No indications of human reproductive toxicity exist.

#### Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

### STOT-single exposure

See SECTION 2.1 (classification).

### STOT-repeated exposure

See SECTION 2.1 (classification).

### Aspiration hazard

See SECTION 2.1 (classification).

## SECTION 12: Ecological information

### 12.1 Toxicity

Data apply to the main component. There are no data available on the preparation/mixture itself.

#### Aquatic toxicity

##### Acute (short-term) algae toxicity

Parameter : EC50 ( FORMIC ACID ; CAS No. : 64-18-6 )  
Species : Daphnia  
Effective dose : 120 mg/l  
Exposure time : 48 h

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin CEMENT-AWAY

**Revision date :** 30.01.2019

**Version (Revision) :** 4.0.2 (4.0.1)

**Print date :** 11.02.2019

## Effects in sewage plants

Observe local regulations concerning effluent treatment. Before discharge into sewage plants the product normally needs to be neutralised.

## 12.2 Persistence and degradability

There are no data available on the preparation/mixture itself.

### Biodegradation

The surfactant contained in this mixture complies with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

## 12.3 Bioaccumulative potential

There are no data available on the preparation/mixture itself.

## 12.4 Mobility in soil

There are no data available on the preparation/mixture itself.

## 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6 Other adverse effects

There are no data available on the preparation/mixture itself.

## 12.7 Additional ecotoxicological information

### Additional information

The product has not been tested.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Dispose according to legislation.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

### Product/Packaging disposal

#### Waste codes/waste designations according to EWC/AVV

##### Waste code product

Waste code (EWC/AVV) : 06 01 06\*

##### Waste code packaging

Waste code packaging: 15 01 10\*

#### Waste treatment options

29/35 - Do not empty into drains; dispose of this material and its container in a safe way. Delivery to an approved waste disposal company.

#### Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

### 13.2 Additional information

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

## SECTION 14: Transport information

### 14.1 UN number

UN 1760

### 14.2 UN proper shipping name

#### Land transport (ADR/RID)

CORROSIVE LIQUID, N.O.S. ( HYDROCHLORIC ACID · FORMIC ACID )

#### Sea transport (IMDG)

CORROSIVE LIQUID, N.O.S. ( HYDROCHLORIC ACID · FORMIC ACID )

#### Air transport (ICAO-TI / IATA-DGR)



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin CEMENT-AWAY

Revision date : 30.01.2019

Version (Revision) : 4.0.2 (4.0.1)

Print date : 11.02.2019

CORROSIVE LIQUID, N.O.S. ( HYDROCHLORIC ACID · FORMIC ACID )

## 14.3 Transport hazard class(es)

### Land transport (ADR/RID)

Class(es) : 8  
Classification code : C9  
Hazard identification number (Kemler No.) : 80  
Tunnel restriction code : E  
Special provisions : LQ 1 | · E 2  
Hazard label(s) : 8

### Sea transport (IMDG)

Class(es) : 8  
EmS-No. : F-A / S-B  
Special provisions : LQ 1 | · E 2 · IMDG-Code segregation group 1 - Acids  
Hazard label(s) : 8

### Air transport (ICAO-TI / IATA-DGR)

Class(es) : 8  
Special provisions : E 2  
Hazard label(s) : 8

## 14.4 Packing group

II

## 14.5 Environmental hazards

Land transport (ADR/RID) : No  
Sea transport (IMDG) : No  
Air transport (ICAO-TI / IATA-DGR) : No

## 14.6 Special precautions for user

None

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not required.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (clp)

Directive 2008/98/EC of the European Parliament and of the Council on waste (2000/532/EC)

EN 2:1992 (DIN EN 2:2005-01)

#### Authorisations and/or restrictions on use

##### Restrictions on use

Use restriction according to REACH annex XVII, no. : None, if handled according to order.

##### Restrictions of occupation

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).  
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

#### Other regulations (EU)

Regulation (EC) No. 648/2004 (Detergents regulation)

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work. (Directive 2000/39/EC, Directive 2006/15/EC, Directive 2009/161/EC)

REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the export and import of hazardous chemicals [PIC-Regulation]

REGULATION (EU) No 98/2013 on the marketing and use of explosives precursors: Not applicable.

**Regulation (EC) No. 1005/2009 on substances that lead to the depletion of the ozone layer**

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin CEMENT-AWAY

**Revision date :** 30.01.2019

**Version (Revision) :** 4.0.2 (4.0.1)

**Print date :** 11.02.2019

Not applicable.

Contains the following substances that deplete the ozone layer: -

**Regulation (EC) No 850/2004 [POP-Regulation]**

Not applicable.

Name of the persistent organic pollutant (POP): -

**National regulations**

Observe in addition any national regulations!

Germany:

TRGS 400 (Risk assessment for activities involving hazardous substances)

TRGS 500 (Protective measures)

TRGS 510 (Storage of hazardous substances in non-stationary containers)

TRGS 555 (Working instruction and information for workers)

**Water hazard class (WGK)**

Class : 1 (Slightly hazardous to water) Classification according to AwSV

**Other regulations, restrictions and prohibition regulations**

**Switzerland**

**VOCV-Regulation**

Maximum VOC content (Switzerland) : < 3 Wt % according to VOCV

## 15.2 Chemical safety assessment

For this substance/mixture a chemical safety assessment has not been carried out.

## 15.3 Additional information

## SECTION 16: Other information

### 16.1 Indication of changes

07. Hints on joint storage - Storage class

### 16.2 Abbreviations and acronyms

|                     |   |
|---------------------|---|
| ABC-Pulver          | Extinguishing powder for fire class A, B and C  |
| ABEK-P1             | combination filter  |
| ADR                 | European Agreement concerning the International Carriage of Dangerous Goods by Road                 |
| AVV                 | Abfallverzeichnis-Verordnung (Waste Regulation)   |
| AWSV                | Ordinance on facilities for the handling of substances hazardous to water                           |
| BGR                 | BG rules and regulations  |
| ca.                 | circa   |
| CAS                 | Chemical Abstract Service   |
| CLP                 | classification, labelling and packaging   |
| CMR                 | Carcinogen, mutagen or toxic for reproduction   |
| DIN                 | German Institute for Standardization  |
| DNEL                | Derived No-Effect Level   |
| EAK/EWC/EAC/CWR/CER | European Waste Catalogue  |
| EC50 / CE50         | Effective Concentration 50%   |
| EG / EC / CE        | European Community  |
| EN                  | European Standard   |
| EUH                 | supplemental hazard statement of the european union   |
| GefStoffV           | Gefahrstoffverordnung (Hazardous Substances Ordinance)  |
| GHS / SGH           | Globally Harmonised System  |
| H-Sätze             | hazard statements   |
| IATA-DGR            | International Air Transport Association-Dangerous Goods Regulations                                 |
| IBC-Code            | International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk |

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

## Trade name : Lithofin CEMENT-AWAY

Revision date : 30.01.2019

Version (Revision) : 4.0.2 (4.0.1)

Print date : 11.02.2019

---

|                 |  |
|-----------------|--|
| ICAO-TI         | International Civil Aviation Organization-Technical Instructions                       |
| IMDG-Code       | International Maritime Dangerous Goods Code  |
| ISO             | International Organization for Standardization   |
| LC50 / CL50     | Lethal Concentration 50%   |
| LD50 / DL50     | Lethal Dose 50%  |
| log P O/W       | Partition coefficient n-octanol/water  |
| MARPOL          | International Convention for the Prevention of Pollution from Ships (marine pollution) |
| NOAEL (DSET)    | No observed adverse effect level   |
| NOEC (CSEO)     | No observed effect concentration   |
| Nr.             | Number   |
| OECD            | Organisation for Economic Co-operation and Development                                 |
| PBT             | persistent, bioaccumulative and toxic  |
| pH              | Potentia hydrogenii  |
| PIC             | prior informed consent   |
| PNEC            | Predicted No-Effect Concentration  |
| POP             | Persistent organic pollutants  |
| P-Sätze         | precautionary statements   |
| REACH           | Registration, Evaluation, Authorisation and Restriction of Chemicals                   |
| RID             | International Carriage of Dangerous Goods by Rail                                      |
| STEL / LECT     | short-term exposure limit  |
| TRGS            | Technische Regeln für Gefahrstoffe (Technical Rules for Hazardous Substances)          |
| TWA / MPT       | time-weighted average  |
| UN/ONU          | United Nations   |
| VOC/COV/VOS/LZO | Volatile Organic Compound  |
| VOCV            | Ordinance on the Incentive Tax on Volatile Organic Compounds (SR 814.018)              |
| vPvB            | very persistent and very bioaccumulative   |
| WGK             | Wassergefährdungsklasse (Water hazard class)   |

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>. For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

### 16.3 Key literature references and sources for data

Regulation (EC) No 1272/2008 (GHS)  
ECHA: Registered substances (<https://echa.europa.eu/information-on-chemicals/registered-substances>)  
REACH Art. 59: -Candidate List of substances of very high concern for Authorisation (<https://www.echa.europa.eu/candidate-list-table>)

### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard statements for physical hazards : On basis of test data.  
Hazard statements for health hazards : Calculation method.  
Hazard statements for environmental hazards : Calculation method.

### 16.5 Relevant H- and EUH-phrases (Number and full text)

|      |  |
|------|--|
| H226 | Flammable liquid and vapour.             |
| H290 | May be corrosive to metals.              |
| H314 | Causes severe skin burns and eye damage. |
| H318 | Causes serious eye damage.               |
| H335 | May cause respiratory irritation.        |

### 16.6 Training advice

None

### 16.7 Additional information

None

# Safety Data Sheet

( EN / D )

according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** Lithofin CEMENT-AWAY

**Revision date :** 30.01.2019

**Version (Revision) :** 4.0.2 (4.0.1)

**Print date :** 11.02.2019

---

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---