	fety Data She			(EN / D)
acc	ording to Regulat	tion (EC) No. 190	07/2006 (REACH)	
Tra	ade name :	Lithofin S	V 2K (Curing Agent)	
	sion date : t date :	12.08.2022 07.10.2022	Version (Revision) :	6.0.1 (6.0.0)
SEC	CTION 1: Identific	ation of the sub	stance/mixture and of the company/ un	dertaking
1.1	Product identifie	er		
	Lithofin SV 2K (Curing			
1.2	Relevant identif Relevant identi		ubstance or mixture and uses advised a	gainst
	Mixture PC 0.87 - Ha			
	Remark			
	•	ded for professional use	e.	
1.3	Supplier			
	Contact :			
	Supplier :		Lithofin AG	
	Street :		Heinrich-Otto-Str. 36	
	Postal code/City	:	73240 Wendlingen	
	Telephone :		+49 (0)7024 9403-0	
	Telefax :		+49 (0)7024 9403-40	
	Contact :		Technical Department E-mail: info@lithofin.de	
			Emergency telephone number: +49 (0)7024 9403-0 (Only available during office hours)	
1.4	Emergency telep see section 1.3	ohone number	(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
CE/	CTION 2: Hazards	identification		
SEL	LIION 2: Hazarus	identification		
2.1	Classification of			
			ulation (EC) No 1272/2008 [CLP] tive) : Category 4 ; Harmful if inhaled.	
		, ,	ategory 1 ; May cause an allergic skin reaction.	
			: Category 3 ; May cause respiratory irritation.	
	Aquatic Chronic 3 ; effects.	H412 - Hazardous to th	e aquatic environment : Chronic 3 ; Harmful to aquatic li	ife with long lasting
	Additional info			
		fied as hazardous acco	rding to regulation (EC) No 1272/2008 [CLP].	
	Remark	and Filling and Filling		
רר	For full text of Haza	ra- and EU Hazard-state	ements: see SECTION 16.	
2.2		ding to Pogulati	on (EC) No. 1272/2008 [CLP]	
	Hazard pictogram		UII (LC) NU. 12/2/2000 [CLF]	
		-		



Exclamation mark (GHS07) Signal word Warning Hazard components for labelling

Safety Data Sh		907/2006 (REACH)	(EN /
		307/2000 (REACH)	
rade name :	Lithofin	SV 2K (Curing Agent)	
vision date :	12.08.2022	Version (Revision) :	6.0.1 (6.0.
int date :	07.10.2022		
HEXAMETHYLENE- Hazard statemen H332 H317 H335 H412 Precautionary st P102 P271 P280 P312 P302+P352 P405 P501 Special rules for EUH204 3 Other hazards	DI-ISOCYANATE ; CAS Harmful if inhale May cause an ai May cause respi Harmful to aqua atements Keep out of read Use only outdoo Wear protective Call a POISON (IF ON SKIN: Wa Store locked up Dispose of contr supplemental labe	ed. llergic skin reaction. iratory irritation. atic life with long lasting effects. ch of children. ors or in a well-ventilated area. gloves and eye/face protection. CENTER/doctor/ if you feel unwell. ash with plenty of soap and water.	lations.
None			
4 Additional info	mation		
	macion		
see section 12.5			
CTION 2. Compo	sition /informat	ion on ingredients	
	Sition/ informat		
2 Mixtures			
Hazardous ingred	ionts		
-		BEACH No. + Dolymor + EC No. + EQ0.060.2+ CAS No. + 281	07 01 7
		; REACH No. : Polymer ; EC No. : 500-060-2; CAS No. : 281	02-01-2
Weight fraction :		95 - < 100 %	
Classification 1272	, , ,	ute Tox. 4 ; H332 Skin Sens. 1 ; H317 STOT SE 3 ; H335	
HEXAMETHYLENE-D	I-ISOCYANATE ; REAC	H No. : 01-2119457571-37-xxxx ; EC No. : 212-485-8; CAS N	lo. : 822-06-0
Weight fraction :	≥ (0,05 - < 0,5 %	
Classification 1272		ıte Tox. 2; H330 Resp. Sens. 1; H334 Acute Tox. 4; H302 in Sens. 1; H317 Eye Irrit. 2; H319 STOT SE 3; H335	Skin Irrit. 2 ; H315
Specific Conc. Lim		sp. Sens. 1 ; H334: $C \ge 0.5 \%$ • Skin Sens. 1 ; H317: $C \ge 0.5$	5 %
·			
according to Artic		f very high concern (SVHC) which are included in t	
•			
None (below the co	,		
Contains the follo according to Anno		f very high concern (SVHC) which are subject to au	Ithorisation
None (below the co			
Additional inform	,		
		stered according to REACH regulation.	
-		ements: see SECTION 16.	
		ements. see Section 10.	
CTION 4: First ai	d measures		
=	irst aid measur	es	
General inform			
	e		
		ved, get medical advice. Never give anything by mouth to inscious but breathing normally, place in recovery position	

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

Trade name :

Revision date : Print date :

Lithofin SV 2K (Curing Agent)

12.08.2022 07.10.2022

Version (Revision) :

6.0.1 (6.0.0)

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. Do not wash with: Cleaning agent, acidic Cleaning agent, alkaline Solvents/Thinner

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

Following ingestion

Call a physician immediately. Keep at rest. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

- 4.2 Most important symptoms and effects, both acute and delayed No information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Notes for the doctor

Treat symptomatically. Special treatment

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray jet ABC-powder Foam

Unsuitable extinguishing media

Full water jet Strong water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide Carbon dioxide (CO2) Hydrogen cyanide (hydrocyanic acid)

5.3 Advice for firefighters

Use suitable breathing apparatus.

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases. The product itself does not burn. Coordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment (refer to section 8). Provide adequate ventilation. Remove persons to safety.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For cleaning up

Suitable material for taking up: Universal binder Clean contaminated articles and floor according to the environmental legislation. Retain contaminated washing water and dispose it. Dispose of waste according to applicable legislation.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Trade name :

Revision date : Print date :

Lithofin SV 2K (Curing Agent)

12.08.2022 07.10.2022 Version (Revision) :

6.0.1 (6.0.0)

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

When using do not eat, drink, smoke, sniff.

Protective measures

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists Skin contact Eye contact Wear personal protection equipment (refer to section 8). Always close containers tightly after the removal of product. Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Technical measures and the application of suitable work processes have priority over personal protection equipment.

Measures to prevent fire

The product is not: Flammable Usual measures for fire prevention.

Fire class :	В
Shake well before use	No

Advices on general occupational hygiene

P362+P364 - Take off contaminated clothing and wash it before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep/Store only in original container. The floor should be leak tight, jointless and not absorbent. Ensure adequate ventilation of the storage area.

Hints on joint storage

Storage class (TRGS 510): 10 Recommended storage temperature 5 - 25 °C Protect from frost No

Further information on storage conditions

Keep locked up and out of reach of children. Keep container tightly closed in a cool, well-ventilated place.

7.3 Specific end use(s)

Recommendation

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

HEXAMETHYLENE-DI-ISOCYANATE ; CAS No. : 822-06-0

Limit value type (country of origin) : BAT (CH)

Parameter : Limit value : Version :	Hexamethylenediamine (after hydrolysis) / Urine (U) / End of exposure or end of shift 15 $\mu g/g$ Creatinine
Limit value type (country of origin) :	TRGS 900 (D)
Limit value :	0,005 ppm / 0,035 mg/m ³
Peak limitation :	1/=2=(I)
Remark :	Sa
Version:	02.07.2021
Limit value type (country of origin) :	TRGS 903 (D)
Parameter :	Hexamethylenediamine (after hydrolysis) / Urine (U) / End of exposure or end of shift
Limit value :	0,15 mg/g Creatinine
Version:	04.05.2021

DNEL-/PNEC-values

DNEL/DMEL

Hexamethylenediisocyanate, homopolymer ; CAS No. : 28182-81-2

(EN/D) Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Lithofin SV 2K (Curing Agent) Trade name : Revision date : 12.08.2022 Version (Revision) : 6.0.1 (6.0.0) Print date : 07.10.2022 Limit value type : DNEL worker (local) Exposure route : Dermal Exposure frequency : Short-term Limit value : 1 mg/m^3 Limit value type : DNEL worker (local) Exposure route : Dermal Exposure frequency : Lona-term Limit value : 0,5 mg/m³ HEXAMETHYLENE-DI-ISOCYANATE ; CAS No. : 822-06-0 Limit value type : DNEL worker (local) Exposure route : Inhalation Exposure frequency : Long-term Limit value : 0,035 mg/m³ DNEL worker (systemic) Limit value type : Exposure route : Inhalation Exposure frequency : Short-term Limit value : 0,07 mg/m³ Limit value type : DNEL worker (systemic) Inhalation Exposure route : Exposure frequency : I ona-term Limit value : 0,035 mg/m³ PNFC Hexamethylenediisocyanate, homopolymer ; CAS No. : 28182-81-2 Limit value type : PNEC (Aquatic, freshwater) Limit value : 0,199 ma/l Limit value type : PNEC (Aquatic, marine water) Limit value : 0,0199 mg/l Limit value type : PNEC (Sediment, freshwater) Limit value : 44551 mg/kg PNEC (Sediment, marine water) Limit value type : Limit value : 4455 mg/kg Limit value type : PNEC (Sewage treatment plant) Limit value : 100 mg/l HEXAMETHYLENE-DI-ISOCYANATE ; CAS No. : 822-06-0 Limit value type : PNEC (Aquatic, freshwater) Limit value : > 0,0774 mg/l Limit value type : PNEC (Aquatic, marine water) Limit value : > 0,00774 mg/l Limit value type : PNEC (Sediment, freshwater) Limit value : > 0,01334 mg/kg PNEC (Sediment, marine water) Limit value type : > 0,00133 mg/kg Limit value : Limit value type : PNEC (Sewage treatment plant) Limit value : 8,42 mg/l 8.2 Exposure controls Appropriate engineering controls Ensure adequate ventilation of the storage area. Technical measures and the application of suitable work processes have priority over personal protection equipment. Personal protection equipment Eye/face protection Suitable eye protection Eye glasses with side protection goggles **Required properties** EN 166 Skin protection Hand protection

Trade name :

Revision date : Print date :

Lithofin SV 2K (Curing Agent)

12.08.2022 07.10.2022 Version (Revision) :

6.0.1 (6.0.0)

Suitable gloves type : Gloves with long cuffs

Suitable material : Data apply to the main component. Butyl caoutchouc, 0,5mm, >8h; FKM (fluoro rubber), 0,7mm, >8h;

Recommended glove articles : Manufacturer KCL GmbH/Eichenzell-Germany; Ansell/Yarra City-Australia Or comparable articles from other companies.

Additional hand protection measures : Check leak tightness/impermeability prior to use.

Remark : Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams are not substitutes for body protection.

Body protection

Protective clothing.

Suitable protective clothing : Chemical protection clothing Chemical resistant safety shoes

Required properties : alkali-resistant.

Protective clothing. : EN 13034 EN 14605

Chemical resistant safety shoes : EN ISO 20345

Remark : Barrier creams are not substitutes for body protection.

Respiratory protection

Usually no personal respirative protection necessary. Respiratory protection necessary at: insufficient ventilation aerosol or mist formation. high concentrations spray application

Suitable respiratory protection apparatus

Combination filtering device Half-face mask ABEK-P1

Remark

Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

General information

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to re-use. Wash hands before breaks and after work. Apply skin care products after work. Do not breathe gas/fumes/vapour/spray.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance :	viscous					
Colour :	light yellow					
Odour :	odourless					
Safety charact	eristics					
Melting point/freez	zing point :	(1013 hPa)	<	-13	°C	
Initial boiling point range :	t and boiling	(1013 hPa)	>	250	°C	
Decomposition terr	perature :	(1013 hPa)		not determined		
Flash point :			>	190	°C	closed cup (EN ISO 3679)
Auto-ignition temp	erature :			not determined		
Sustaining combus	tion			No		UN Test L2:Sustained combustibility test
Lower explosion lin	nit :			not determined		
Upper explosion lin	nit :			not determined		
Vapour pressure :		(50 °C)	<	3000	hPa	
Density :		(20 °C)		1,15	g/cm ³	Pyknometer (DIN EN ISO 2811-1)
Solvent separation	test :	(20 °C)	<	3	%	Test L1: Solvent separation test (UN)
Water solubility		(20 °C)		hydrolysed		
pH :				not applicable		DIN 19268

(EN/D)

23 mars 2011

Trade name :

Revis Print

Lithofin SV 2K (Curing Agent)

ision date : t date :	12.08.2022 07.10.2022	-	Version (Revi	ision) :	6.0.1 (6.0.0)
log P O/W :			not determined		(Mixture)
Flow time :	(23 °C)	approx.	500	S	ISO cup 4 mm (DIN EN ISO 2431)
Odour threshold :			not determined		
Vapourisation rate	:		not determined		
VOC content-EC			0	Weight-%	*
VOC-France			not applicable		Décret no 2011-321 du

VOC-France

(* VOC-EC = "Volatile organic compound (VOC)" means any organic compound having an initial boiling point less than or equal to 250°C measured at a standard pressure of 101,3 kPa; VOC-value in g/L)

not applicable

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

Stable under recommended storage and handling conditions.

10.5 Incompatible materials

The product develops hydrogen in an aqueous solution in contact with metals.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful by inhalation.	
Acute oral toxicity	
Parameter :	LD50
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2000 mg/kg
Acute dermal toxicity	
Parameter :	LD50 (Hexamethylenediisocyanate, homopolymer; CAS No.: 28182-81-2)
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 2000
Method :	OECD 402
Parameter :	LD50 (HEXAMETHYLENE-DI-ISOCYANATE ; CAS No. : 822-06-0)
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 7000 mg/kg
Method :	OECD 402
Acute inhalation toxicity	
Parameter :	LC50
Exposure route :	Inhalation
Species :	Rat

Trade name :

Revision date : Print date :

Lithofin SV 2K (Curing Agent)

12.08.2022 07.10.2022 Version (Revision) :

6.0.1 (6.0.0)

Effective dose :	390 mg/m ³
Exposure time :	4 h
Method :	OECD 403
Specific effects (Lon	igterm animal experiment)
There are no data available	e on the preparation/mixture itself.
Corrosion	
Based on available data, the	e classification criteria are not met.
Respiratory or skin s	sensitisation
May cause an allergic skin r	reaction.
Repeated dose toxic	city (subacute, subchronic, chronic)
There are no data available	e on the preparation/mixture itself.
CMR effects (carcino	ogenicity, mutagenicity and toxicity for reproduction)
Carcinogenicity	
	he classification criteria are not met.
Germ cell mutagenicity	
	he classification criteria are not met.
Reproductive toxicity	he classification criteria are not met.
STOT-single exposu	
May cause respiratory irrita	
STOT-repeated expo	
	e classification criteria are not met.
Aspiration hazard	a classification svitaria are not mot
1	e classification criteria are not met.
Information on other	rnazards
No information available.	
TION 12: Ecological in	A

12.1 Toxicity

Toxicity	
Aquatic toxicity	
Harmful to aquatic life with long las	ting effects.
Acute (short-term) fish toxicity	
Parameter :	LC50
Species :	Acute (short-term) fish toxicity
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	28,3 mg/l
Exposure time :	96 h
Method :	OECD 203
Acute (short-term) toxicity to c	rustacea
Parameter :	EC50
Species :	Acute (short-term) toxicity to crustacea
Evaluation parameter :	Acute (short-term) toxicity to crustacea
Effective dose :	> 100 mg/l
Exposure time :	48 h
Method :	OECD 202
Acute (short-term) toxicity to a	lgae and cyanobacteria
Parameter :	IC50
Species :	Acute (short-term) toxicity to algae and cyanobacteria
Evaluation parameter :	Acute (short-term) toxicity to algae and cyanobacteria
Effective dose :	> 100 mg/l
Exposure time :	72 h
Method :	OECD 201

Lithofin SV 2K (Curing Agent) Trade name : Revision date : 12.08.2022 Version (Revision) : Print date : 07.10.2022 Sewage treatment plant Observe local regulations concerning effluent treatment. Before discharge into sewage plants the product normally needs to be neutralised.

12.2 Persistence and degradability

There are no data available on the preparation/mixture itself.

Biodegradation

There are no data available on the preparation/mixture itself.

12.3 Bioaccumulative potential

There are no data available on the preparation/mixture itself.

12.4 Mobility in soil

There are no data available on the preparation/mixture itself.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties No information available.

12.7 Other adverse effects

There are no data available on the preparation/mixture itself.

12.8 Additional ecotoxicological information

Additional information

The product has not been tested.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of waste according to applicable legislation.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Waste codes/waste designations according to EWC/AVV

Waste code (EWC/AVV): 08 05 01* (Waste isocyanates)

After intended use

Do not allow to enter into surface water or drains. Non-contaminated packages may be recycled. Packing which cannot be properly cleaned must be disposed of. Delivery to an approved waste disposal company.

Disposal operations

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

Waste codes/waste designations according to EWC/AVV

Waste code packaging: 15 01 10*

13.2 Additional information

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

6.0.1 (6.0.0)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name :

Lithofin SV 2K (Curing Agent)

Revision date : Print date :

12.08.2022 07.10.2022

Version (Revision) :

6.0.1 (6.0.0)

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

- None
- **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not required.

SECTION 15: Regulatory information

^{15.1} Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on classification, labelling and packaging of substances and mixtures (clp)

DIRECTIVE 2008/98/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on waste (2000/532/EC) EN 2:1992 (DIN EN 2:2005-01)

Authorisations and/or restrictions on use

Restrictions on use

Use restriction according to REACH annex XVII, no.: 3, 74, 75

Restrictions of occupation

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Other regulations (EU)

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work. (Directive 2000/39/EC, Directive 2006/15/EC, Directive 2009/161/EC)

REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the export and import of hazardous chemicals [PIC-Regulation]: Not listed/not relevant.

REGULATION (EU) No 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on the marketing and use of explosives precursors: Not listed/not relevant.

Regulation (EC) No. 1005/2009 on substances that lead to the depletion of the ozone layer

Not listed/not relevant.

Contains the following substances that deplete the ozone layer: -

Regulation (EC) 2019/1021 [POP Regulation]

Not listed/not relevant.

Name of the persistent organic pollutant (POP): -

National regulations

Observe in addition any national regulations!

Germany:

TRGS 400 (Risk assessment for activities involving hazardous substances)

TRGS 500 (Protective measures)

TRGS 510 (Storage of hazardous substances in non-stationary containers)

TRGS 555 (Working instruction and information for workers)

Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

Other regulations, restrictions and prohibition regulations

Switzerland

VOCV-Regulation

Maximum VOC content (Switzerland): 0 Weight-% according to VOCV

Austria

Regulation on Flammable Liquids - VbF VbF-Class : NU

15.2 Chemical Safety Assessment

For this substance/mixture a chemical safety assessment has not been carried out.

Safety Data She		(EN / C
ccording to Regula	tion (EC) No. 1907/2006 (REACH)	
[rade name :	Lithofin SV 2K (Curing Agont)	
evision date :	Lithofin SV 2K (Curing Agent)	6 0 1 (6 0 0
evision date : rint date :	12.08.2022 Version (Revision) : 07.10.2022	6.0.1 (6.0.0
5.3 Additional infor	mation	
ECTION 16: Other i	nformation	
6.1 Indication of ch	anges	
07. Hints on joint sto	-	
6.2 Abbreviations a	nd acronyms	
ABC-Pulver	Extinguishing powder for fire class A, B and C	
ABEK-P1	combination filter	
ADR	European Agreement concerning the International Carriage of Dangerous (Goods by Road
AVV	Abfallverzeichnis-Verordnung (Waste Regulation)	
AWSV	Ordinance on facilities for the handling of substances hazardous to water	
BGR	BG rules and regulations	
ca.	circa	
CAS	Chemical Abstracts Service	
CLP	classification, labelling and packaging	
CMR	Carcinogen, mutagen or toxic for reproduction	
DIN	German Institute for Standardization	
DNEL	Derived No-Effect Level	
EAK/EWC/EAC/CWR/	CER European Waste Catalogue	
EC50 / CE50	Effective Concentration 50%	
EG / EC / CE	European Community	
EN	European Standard	
EUH	supplemental hazard statement of the european union	
GefStoffV	Gefahrstoffverordnung (Hazardous Substances Ordinance)	
GHS / SGH	Globally Harmonised System	
H-Sätze	hazard statements	
IATA-DGR	International Air Transport Association-Dangerous Goods Regulations	
IBC-Code	International Code for the Construction and Equipment of Ships carrying D Chemicals in Bulk	angerous
ICAO-TI	International Civil Aviation Organization-Technical Instructions	
IMDG-Code	International Maritime Dangerous Goods Code	
ISO	International Organization for Standardization	
LC50 / CL50	Lethal Concentration 50%	
LD50 / DL50	Lethal Dose 50%	
log P O/W	Partition coefficient n-octanol/water	
MARPOL	International Convention for the Prevention of Pollution from Ships (marine	e pollution)
NOAEL (DSET)	No observed adverse effect level	
NOEC (CSEO)	No observed effect concentration	
Nr.	Number	
OECD	Organisation for Economic Co-operation and Development	
PBT	persistent, bioaccumulative and toxic	
рН	Potentia hydrogenii	
PIC	prior informed consent	
PNEC	Predicted No-Effect Concentration	
POP	Persistent organic pollutants	
P-Sätze	precautionary statements	

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

Lithofin SV 2K (Curing Agent) Trade name :

Revision date :	12.08.2022	Version (Revision) :	6.0.1 (6.0.0)
Print date :	07.10.2022		

REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	International Carriage of Dangerous Goods by Rail
STEL / LECT	short-term exposure limit
TRGS	Technische Regeln für Gefahrstoffe (Technical Rules for Hazardous Substances)
TWA / MPT	time-weighted average
UN/ONU	United Nations
VOC/COV/VOS/LZO	Volatile Organic Compound
VOCV	Ordinance on the Incentive Tax on Volatile Organic Compounds (SR 814.018)
vPvB	very persistent and very bioaccumulative
WGK	Wassergefährdungsklasse (Water hazard class)

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu. For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

16.3 Key literature references and sources for data

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL ECHA: Registered substances (https://echa.europa.eu/information-on-chemicals/registered-substances) REACH Article 59: Candidate List of substances of very high concern for Authorisation (https://echa.europa.eu/candidate-list-table)

$_{16.4}$ Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard statements for physical hazards : On basis of test data. Hazard statements for health hazards : Calculation method. Hazard statements for environmental hazards : Calculation method.

16.5 Relevant H- and EUH-phrases (Number and full text)

itereraite in	
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
	-

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.